


HOLE TAPPED M16 X 36mm DEEP TO DIN 332 FORM 'D'

DRAIN HOLES:- WHEN TERMINAL BOX IS MOVED FROM STANDARD POSITION THEY WILL NEED TO BE PLUGGED AND RE-LOCATED ELSEWHERE - IF REQUIRED
 TERMINAL BOX POSITION : - CAN BE ARRANGED AT EITHER 9, 12 OR 3 O' CLOCK BY MOVING FEET.
 CONDUIT ENTRIES:- TERMINAL BOX CAN BE ROTATED AT 90° INTERVALS (CONDUIT ENTRY POSITION SHOWN FOR ILLUSTRATION ONLY).

ALL DIMENSIONS IN MILLIMETRES



FIRST ANGLE PROJECTION

BROOK CROMPTON

Produced by *Tamel s.a.* a company of **ATB** Technology in Motion

SHEET SIZE A3	TITLE	NAME	DATE	DRG. No. W41GF0119T	
	OUTLINE DIMENSION DRAWING W CAST IRON TOTALLY ENCLOSED FAN COOLED 160M/L FRAME FOOT MOUNTED MOTOR - TERMINAL BOX TOP	JM	29-03-11	DRG. REF.	
				REVISION:	DATE
		SCALE 1:5			