

Three-phase asynchronous motor

MOTOR FRAME: **Aluminium**

a company of



Motor type: **WU-DA180ME IE2 2P 22 kW B3**
 Motor item number: **180W477200T**

Rated power:	22 kW				kW
Poles(Synch speed):	2p (3000) r.p.m				r.p.m
Full load speed:	2950 r.p.m				r.p.m
Voltage:	400	/	690	V	V
Frequency:	50 Hz				Hz
Connection:	Δ	/	Y		
Amps full load (FLA):	39	/	22,5	A	A
Amps no-load (NLA):					A

Enclosure:	IP55		Cable entries size:	2 x CM32	
Mounting:	IM B3 (IM 1001)		Winding protection:		
Insulation Class:	F		Max. Altitude:	1000	m.a.s.l.
Max. ambient temp.:	+40	°C	Heater:	no	
Min. ambient temp.:	-20	°C	Shaft extension:	48x110	mm
Max. temp. rise:	80	K	Weight:	118	kg
Duty type:	S1		Painting:	Alkyd-Amin Resins Paint	
Cooling form:	IC411 (TEFC)		Color:	RAL 5021	
Bearing DE	6310	ZZ C3	Box position:	Top DE	
Bearing NDE	6308	ZZ C3	Cable entry towards:	Right	
Grease:	Lithium or Polyurea Base		Cable type:	N/A	
Regreasing facilities:	NO		Balance grade:	Normal	

Efficiency class:	IE2			Sound pressure (1m):	68 dB(A)
Load data:	100%	75%	50%	Resistance R20:	0,32 PH
Efficiency:	91,3	91,5	90,4		
Power factor:	0,89	0,86	0,76		

Full load torque (FLT):	71,2	Nm	Pull out torque ratio:	3,1	MK/MN
Starting torque ratio:	2,2	MA/MN	Pull up torque:	1,9	MS/MN
Starting current ratio:	9,0	IA/IN	Rotor inertia WK2:	0,084	kgm²

Special remarks:

SPECIAL DATA FOR HAZARDOUS LOCATION MOTOR

Hazardous classification:	Temp. Class:	
Certificate number:	t _E time:	sek

Special remarks: