

Three-phase asynchronous motor

MOTOR FRAME: Cast Iron

a company of 

Motor type: WU-DF90LWX-D IE2 4P 1,5kW B5
Motor item number: 090W227511T

50 HZ data	Rated power:	1,5 kW			60 HZ data	kW
	Poles(Synch speed):	4p (1500) r.p.m				r.p.m
	Full load speed:	1440 r.p.m				r.p.m
	Voltage:	230	/	400 V		V
	Frequency:	50 Hz				Hz
	Connection:	Δ	/	Y		
	Amps full load (FLA):	6,5	/	3,7 A		A
	Amps no-load (NLA):	A				

Enclosure:	IP55	Cable entries size:	1 x CM20
Mounting:	IM B5 (IM 3001)	Winding protection:	
Insulation Class:	F	Max. Altitude:	1000 m.a.s.l.
Max. ambient temp.:	+40 °C	Heater:	no
Min. ambient temp.:	-20 °C	Shaft extension:	24x50 mm
Max. temp. rise:	80 K	Weight:	kg
Duty type:	S1	Painting:	Argus
Cooling form:	IC411 (TEFC)	Color:	RAL 5021
Bearing DE	6205 ZZ CM	Box position:	Top DE
Bearing NDE	6203 ZZ CM	Cable entry towards:	Right
Grease:	Lithium or Polyurea Base	Cable type:	N/A
Regreasing facilities:	NO	Balance grade:	Normal

Efficiency class:	IE2	Sound pressure (1m):	48 dB(A)
Load data:	100% 75% 50%	Resistance R20:	2,52 PH
Efficiency:	82,8 83 81		
Power factor:	0,70 0,58 0,46		

Full load torque (FLT):	9,9 Nm	Pull out torque ratio:	3,1 MK/MN
Starting torque ratio:	2,6 MA/MN	Pull up torque:	2,4 MS/MN
Starting current ratio:	5,6 IA/IN	Rotor inertia WK2:	0,0042 kgm ²

Special remarks:

SPECIAL DATA FOR HAZARDOUS LOCATION MOTOR

Hazardous classification:	Temp. Class:
Certificate number:	t _E time: sek

Special remarks: